

INCIDENT ALERT

LOCATION:	TRANSPORT	ALERT STATUS:	Normal
ACTIVITY:	MAINTENANCE & HOUSEKEEPING	DATE ISSUED:	25/10/2021 17:56:00
SUB ACTIVITY:	N/A	INCIDENT No:	03598

TITLE

FATAL 1 - Safe working on vehicle hydraulic systems - HSENI Alert

COUNTRY OF ORIGIN

ACCIDENT / INCIDENT DETAILS

The Health and Safety Executive for Northern Ireland (HSENI) are reminding all persons responsible for operating and / or maintaining vehicle hydraulics, to ensure safe working practices are in place whilst carrying out maintenance and repair work.

Earlier this year a serious incident occurred whereby an individual suffered life changing injuries whilst working on the vehicle hydraulics on a loading shovel.

ACCIDENT / INCIDENT IMAGES

LEARNING POINTS / ACTIONS TAKEN

Persons responsible must ensure that adequate control measures are in place to allow maintenance and repair work to be carried out to vehicle hydraulics safely.

What you must do

- Always consider whether repair or maintenance work can be completed with the hydraulic attachment resting on the ground. This is the preferred option.
- Where the lifting arms need to be raised, they MUST be adequately supported whilst working underneath. Use the manufacturers locking device - where this is not provided, use a suitable stand or prop to support the arms and hydraulic attachment.
- Always prop cabs and tipping trailers which could fall under their own weight - use a back-up prop when working underneath a raised trailer.
- Ensure the vehicle is parked on a flat level surface, the hand brake is applied, the keys are removed from the ignition, the cab is locked and the keys remain with the person undertaking the work activity at all times. On sloped ground, park the machine with the wheels securely chocked.
- Always release any stored hydraulic pressure in the system before commencing repair or maintenance.
- Follow the specific manufacturer's instructions for repair and maintenance to the hydraulic system. Refer to the machine's operation and maintenance manual.
- Provide the correct equipment for the job. Ensure equipment is maintained in good condition, is under a currently valid scheme of statutory examination and regular inspections are carried out.
- Develop a safe system of work (SSOW) for working on vehicle hydraulics. Ensure any employees involved in the work activity have received adequate information, instruction and training to enable them to perform their work activity safely.
- Where hydraulic repair or maintenance work is subcontracted to an external person, perform a check on their competence, training and experience prior to the commencement of work.

What not to do

- Persons not involved in the repair/ maintenance activity should NOT be in the vicinity.
- Never use defective equipment or exceed the safe working capacity of any equipment used to support a vehicle.
- Never work underneath unsupported lifting arms - a sudden release of hydraulic energy can cause the hydraulic attachment and arms to fall within seconds causing serious injury or a fatality.
- Never work on a pressurised hydraulic system - always release stored energy.
- When checking for hydraulic leaks NEVER use your hands. Ejection of hydraulic fluid can penetrate the skin leading to blood poisoning; cause burns from contact at high temperature and lead to skin irritation.
- **DO NOT** be tempted to take short-cuts.

PLEASE SEE PDF FOR THE FULL HSENI ALERT WITH IMAGES

LEARNING POINTS / ACTIONS IMAGES