

130005 EMEAR

Date: July 29, 2013

Model Affected: Z-135/70

Subject: Secondary Boom Angle Sensor Calibration

Allowable Hours: 60 minutes

Issue:

Genie has become aware of secondary boom angle sensor calibrations performed in the field in which the machine's service manual may not have been followed creating an improperly calibrated machine. An improperly calibrated machine can lead to machine instability resulting in a machine tip over.


Action Required:

This safety notice requires the immediate removal of all Genie Z-135/70 Boom lifts from service. Machines may only be returned to service after the inspection listed below is performed.

Tool required: Properly calibrated Digital level with magnetic base.

Inspection Procedure:

- 1. Locate and remove all of the machine models listed above from service.
- 2. Perform this procedure with the machine on a firm level surface, with the axles extended and the boom in the stowed position.
- 3. Locate the swing chassis.





130005 EMEAR

4. Place the digital level on the swing chassis as shown below.




5. Set the digital level read out to zero.





130005 EMEAR

6. Working on the same side of the machine, move the digital level from the swing chassis to the top of the secondary boom closest to the pivot end as shown below. Do not change the orientation of the digital level.



7. At the ground controls:

- a. Start the engine.
- b. Fully raise the secondary boom until any one of the inner boom sections just starts to extend.
- c. Stop extending and turn the engine off.

Note: If the digital level times out before the secondary boom is fully raised, repeat the procedure from step 4.

- 8. Record the value displayed on the digital level in the attached "Completion Form".
 - If the value is greater than or equal to (≥) 75.5°, the machine is safe to use and can be returned to service. Finish filling out the "Completion Form" and return to Genie. No further action is required.
 - ⊗ If the value is less than (<) 75.5 °, the machine must remain out of service. The secondary boom angle sensor will need to be calibrated. Continue on to step 9.
 </p>



130005 EMEAR

9. Calibrate the secondary angle sensor of the machine per the instructions in the machine's service manual (section 4-9). Record the desired digital level reading, greater than or equal to (≥) 75.5 °, after calibration in the attached Completion Form.

Note: Do not perform this procedure unless you are trained and qualified to do so. To search for your nearest Terex AWP authorized dealer, click the link below:

http://www.genielift.com/dealersearch

- 10. Return the machine to service.
- 11. Finish filling out the "Completion Form" and return to Terex AWP Warranty Department. This will serve as verification that you have completed Safety Notice 130005.

Warranty:

The labor and travel distance required to perform this inspection and installation are covered under the provisions of our warranty agreement. Warranty claims can be submitted online, fax or e-mail. Please combine as many machines as possible on one claim form. If you need more information about filing a warranty claim, call Terex AWP warranty department.

If you are the owner of an affected machine and are not an authorized Terex AWP dealer, please contact your nearest Terex AWP dealer for assistance in completing this bulletin. Only Terex AWP Authorized Dealers will be reimbursed for labor or any other costs associated with this bulletin under the provisions of our standard warranty terms and conditions.

Local norms and regulations require that the seller of a Genie machine report to Genie the model and serial number of each machine sold, as well as the name, address, and telephone number of the new owner, within 60 days of the sale.

UK: 00 44 1476 584 333
France: 00 33 237 260 986
Germany: 00 49 422 149 1821
Iberica: 0034 900 808 110
Italy: 0039 075 941 8171
Sweden: 0046 3157 5101
Middle East: 0097 143 391 381 or

0097 150 459 7937

All other locations: 0031 653 221 908

Enclosures:

Machine List Report New Owner Update Form Completion Form



New Owner Information:

Safety Notice 130005

New Owner Update Form

(for updating machine owner information only)

Local norms and regulations require that the seller of a Genie machine report to Genie the model and serial number of each machine sold, as well as the name, address, and telephone number of the new owner, within 60 days of the sale.

If you have sold a machine, list new owner's name, address and phone number, for each machine. List complete model and serial number.

Machine 3

0031 165 510 826

All other locations:

Machine 2 Machine 1

Model*		
Serial Number *		
Owner Name*		
Address 1*		
Address 2		
City/State/Zip*		
Phone Number*		
Contact Person		
* Required fields	 	

Seller Information:

Seliei lilloillialioli.	
Date:	
Company Name:	
Account #:	
Address:	
(street)	
(city)	
(state, zip code)	
Phone #	

List any machines that could not be inspected or repaired because of the following:

0046 3157 5104

Sweden:

Model & Serial Number		Scrapped	Exported	Stolen	Other (explain)
				- ⁻	
		<u>-</u>	<u> </u>	- <u>-</u> <u>-</u> -	
			-	-[[-	
Fax To:	UK:	0044 1476 584 330		Middle East:	0097 143 990 382
	France:	0033 237 260 998		Latin America:	001 425 498 7530
	Germany:	0049 4221 491 820		Central America:	001 425 498 7530
	Iberica:	0034 935 725 080		Carribean:	001 425 498 7530
	Italy:	0039 075 941 8146		Mexico:	001 425 498 7530



Completion Form

Your signature on this form will verify that you have performed Safety Notice 130005 and completed the necessary actions before returning the machine to service.

- $oldsymbol{\circ}$ If the digital level reading is greater than or equal to (\geq) 75.5 °, the machine is safe to use and can be returned to service.
- ⊗ If the value is less than (<) 75.5 °, calibrate the secondary boom angle sensor before returning the machine to service. Refer to section 4-9 of the machine's service manual for the calibration procedure.

List the complete model and serial number (example: Z13505-146 or Z13507-556 or Z13512-1750)

Serial Number			1st digital level read-out		2 nd digital level read out after calibration is performed	
Date:						
Company N Account #: Address: (street) (city) State, zip co Phone #:	- - -			- - - - -		
Fax To:	UK: France: Germany: Iberica: Italy: Sweden:	0044 1476 50 0033 237 260 0049 4221 40034 935 720 0039 075 94 0046 3157 5	0 998 91 820 5 080 1 8146	Middle Ea Latin Ame Central Ar Carribean Mexico: All other lo	rica: merica: :	0097 143 990 382 001 425 498 7530 001 425 498 7530 001 425 498 7530 001 425 498 7530 0031 165 510 826
Service	e Manager (Print Name)	_		Signatu	re